

## MULTIKABEL

ORL0301960  
Multikabel 4P 1m

- 4- og 7-pols M16 støpte kontakter
- Utviklet for beste EMC-beskyttelse
- Driftstemperatur fra -40 til +85 °C




### PRODUKTBESKRIVELSE


Orlaco utvikler sin egen kabling for å oppnå best mulig bilde kvalitet og EMC-beskyttelse. Støpte kontakter betyr at de har god fuktighetsbeskyttelse. Multikabelen er beregnet for statisk montering. Dersom du ønsker at kablingen skal brukes til en mobil applikasjon, se serien for dynamiske kabling.

### TEKNISKE DATA

<b>IP-klasse</b>	IP67
<b>Kabeldiameter</b>	6 mm
<b>Kabellengde</b>	1000 mm
<b>Kontakter</b>	4-polt hann, 4-polt hunn
<b>Materiale</b>	PVC
<b>Temperaturområde fra</b>	-40 °C
<b>Temperaturområde til</b>	85 °C
<b>Type</b>	Analog




Front side female connector



Front side male connector

**Electrical connection**

- 1 = Coax core = Video signal
- 2 = Coax shielding = Video GND
- 3 = Red = 12V/DC
- 4 = Black = 0V
- Shielding = GND



Front side molded 7P Female connector



Front side molded 7P Male connector

**Electrical connection molded connectors**

- 1 = Coax Core
- 2 = Coax Shield
- 3 = Red (Power input)
- 4 = Black (0V)
- 5 = Orange (Rx)
- 6 = Yellow (Tx)
- 7 = Grey (Aux)

**Dimensions**

