



USK-M / USK-P

Rørkobling - Rett

5020.330.012

Rørkobling AIRflex USK-M M12x1,5

- vanntett og støv resistent
- Friksjons og vibrasjons tolerant
- IP 54
- -10 °C till +110 °C
- Passer til AirFlex-KUW-PVC-AS og PU-AS



PRODUKTBESKRIVELSE

Materiale	Polypropylen
Temperaturområde	-10 °C till +110 °C
Godkjenninger	



Koblingsdel med sekskantetskiftenøkkeloverflate og tilkoblingstråd.

TEKNISKE DATA

Diameter	14 mm
Farge	Grå
Forpakkingsstørrelse	50 pc
Gjenger	M12x1,5 met. EN 60423
Godkjenninger	CSA 22.2, UL
IP-klasse	IP54
Materiale	Polypropylen
Passer til	AIRFLEX KUW-PU-AS, AIRFLEX KUW-PVZ-AS
Temperaturområde fra	-10 °C
Temperaturområde til	110 °C
Type	USK-M

Vekt kg/100 ±10%

0,66



USK-M

IP54-65	Ø	l mm	B mm	C mm	D mm
5020.330.012	14	8,0	25,0	12,0	43,0
5020.330.016	17	11,0	30,0	12,0	43,0
5020.330.020	21	15,0	35,0	13,0	44,0
5020.330.025	27	20,0	44,0	13,0	50,0
5020.330.032	36	27,0	54,0	15,0	51,0
5020.330.040	45	35,0	63,0	15,0	51,0
5020.330.050	56	44,5	77,0	16,0	58,0
5020.330.063	56	44,5	77,0	16,0	58,0

USK-P

IP54-65	Ø	l mm	B mm	C mm	D mm
5020.130.009*	14	9,0	25,0	10,0	41,0
5020.130.011*	17	11,0	30,0	10,0	41,0
5020.130.013	19	13,0	32,0	10,0	41,0
5020.130.016*	21	14,5	35,0	11,0	42,0
5020.130.021	27	19,5	44,0	11,0	48,0
5020.130.029	36	27,0	54,0	12,0	48,0
5020.130.036	45	36,0	63,0	12,0	48,0
5020.130.048	56	46,0	77,0	15,0	57,0