



NET-BOX PROFINET/PROFISAFE

530001-1
NET-BOX-PS M20 PLAST

- Tre sikkerhetsinnganger med doble kanaler
- Opptil 40 ikke sikre I/O
- Integrrert PROFINET-Switch for sikkerhetsnettverk
- IP65 kapsling





PRODUKTBESKRIVELSE

Kontrollstasjonen NET-BOX-PS med integrert PROFINET med PROFISafe gir opptil 6 konfigurerbare maskinstyringsfunksjoner og 4 ekstra M12-tilkoblinger for feltenheter og distribuert I/O. Det kompakte designet og robuste polyestehuset er egnet for utvendig montering, og gir enkel og kostnadseffektiv tilkobling.

TEKNISKE DATA

Arbeidstemperatur	-20 °C to 40 °C
IP-klasse	IP65
Materiale sentral	Polyester
PL	e
SIL	3
Solenoid Voltage	24 V DC +10%/-15%
Standarder	ISO 13849-1, EN60947-5-3, ISO 14119
Vibrasjon	Tested in accordance with: IEC 60068-2-6 and IEC 60068-2-27



530001 - NETxxxx - 1E - 2BR - 3LG - 4S - 5BW - 6X

530001 - NETxxxx - 1E - 2BR - 3LG - 4S - 5BW - 6X



Illuminated Emergency Stop		Illuminated Push Buttons		Lamps		Illuminated Selector Switch		Blanking Plug	
Control Device Code	Note	Control Device Code	Colour of Lens	Control Device Code	Colour of Lens	Control Device Code	Description	Code	Description
E	E-Stop can only be fitted into Position 1 on Lid.	B	ISSUED BY IDEM FOR ADDITIONAL CONNECTIVITY	L	POSITION ON LID	S	CONTROL DEVICE CODE	X	Blanking Plug used to avoid any missed positions.

Illuminated Emergency Stop		Illuminated Push Buttons		Lamps		Illuminated Selector Switch		Blanking Plug	
Control Device Code	Note	Control Device Code	Colour of Lens	Control Device Code	Colour of Lens	Control Device Code	Description	Code	Description
E	E-Stop can only be fitted into Position 1 on Lid.	B	ISSUED BY IDEM FOR ADDITIONAL CONNECTIVITY	L	POSITION ON LID	S	CONTROL DEVICE CODE	X	Blanking Plug used to avoid any missed positions.