



NET-BOX PROFINET/PROFISAFE RUSTFRITT STÅL

532001-1
NET-BOX-PS-SS M20 RUSTFRITT STÅL

- Tre sikkerhetsinnganger med doble kanaler
- Opptil 40 ikke-sikre I/O
- Integrert PROFINET-switch for sikkerhetsnettverk
- IP65 kapsling (IP69K med knappbeskyttelse)
- Rustfritt stål





PRODUKTBESKRIVELSE

NET-BOX-PS-SS kontrollstasjon med integrert PROFINET med PROFIsafe gir opptil 6 konfigurerbare maskinstyringsfunksjoner og 4 ekstra M12-tilkoblinger for feltenheter og distribuert I/O. Den kompakte designen og det robuste huset i rustfritt stål er egnet for utvendig montering, og gir enkel og kostnadseffektiv tilkobling.

TEKNISKE DATA

Arbeidstemperatur	-20 °C to 40 °C
IP-klasse	IP65
Materiale sentral	Rustfritt stål
PL	e
SIL	3
Solenoid Voltage	24 V DC +10%/-15%
Standarder	ISO 13849-1, EN60947-5-3, ISO 14119
Vibrasjon	Tested in accordance with: IEC 60068-2-6 and IEC 60068-2-27



530001 - NETxxxx - 1E - 2BR - 3LG - 4S - 5BW - 6X

530001 - NETxxxx - 1E - 2BR - 3LG - 4S - 5BW - 6X



Illuminated Emergency Stop		Illuminated Push Buttons		Lamps		Illuminated Selector Switch		Blanking Plug	
Control Device Code	Note	Control Device Code	Colour of Lens	Control Device Code	Colour of Lens	Control Device Code	Description	Code	Description
E	E-Stop can only be fitted into Position 1 on Lid.	B		R		S	SMO Maintained	X	Blanking Plug used to avoid any missed positions.
				G					
				Y					
				B					
				W					

Illuminated Emergency Stop		Illuminated Push Buttons		Lamps		Illuminated Selector Switch		Blanking Plug	
Control Device Code	Note	Control Device Code	Colour of Lens	Control Device Code	Colour of Lens	Control Device Code	Description	Code	Description
E	E-Stop can only be fitted into Position 1 on Lid.	B		R		S	SMO Maintained	X	Blanking Plug used to avoid any missed positions.
				G					
				Y					
				B					
				W					